

## DC Bias Current Sources



**3265B 1 MHz**

**3265BQ 3 MHz**

### Auxiliary Units for 3255B and 3260B series Analyzers

- Enhances usability of Wayne Kerr Analyzers
  - 3255B Inductance Analyzers series
  - 3260B Precision Magnetics Analyzer
- A single DC Bias Unit can deliver between 25 mA and 25 A DC bias current in 25 mA steps
- Available in 1 MHz and 3 MHz versions
- 125 A at 1 MHz measurement frequency
- 50 A at 3 MHz measurement frequency
- DC Bias Fixtures available which allow accurate and safe testing of conventionally leaded and surface mount inductors
- Adds additional functionality
- Up to 10 V Compliance Voltage across the Device Under Test

The instruments have a number of safety and protection features including a safety interlock system to protect the user against back EMFs. They are also fully protected against over temperature, excess voltage drop and sense lead failure.



*3265B with 3260B analyzer*

#### Component tests to 125 A DC bias

To evaluate components at currents up to 125 A the 3265B DC Bias Units are used with either the Wayne Kerr 3255B series of Inductance Analyzers or the 3260B Precision Magnetics Analyzer. When one 3265B DC Bias Unit is connected to an analyzer up to 25 A of DC bias current can be set in steps of 25 mA. Additional DC Bias Units can be added. With five units connected in parallel it is possible to set DC bias currents up to a maximum of 125 A DC.

#### Test Fixtures

Details of the Wayne Kerr DC Bias Test Fixtures may be found at [www.waynekerrtest.com](http://www.waynekerrtest.com). Stable component fixtures ensure high accuracy and repeatable measurements. Enclosed fixtures with safety interlocks minimise any risk to operators. The 1036 Fixture is rated at 250 A and is suitable for conventional components. The 10362 Fixture is suitable for bottom contact surface mount inductors.

## Technical specifications

### Compliance Voltage

Maximum compliance voltage:

Measurement frequency  $\leq$  12 kHz

AC Drive Level must be  $\leq$  100 mV rms when

DC voltage across DUT is 10 V max

Measurement frequency  $>$  12 kHz

AC Drive Level must be  $\leq$  1 V rms when DC

voltage across DUT is 10 V max

### Parameters measured

In Impedance Mode: L, Q, Z,  $\theta$ , R, C, D.

Not applicable to Rdc or transformer measurements

### 3265B Measurement Frequency Range

3255BL: 20 Hz to 200 kHz

3255B: 20 Hz to 500 kHz

3255BQ: 20 Hz to 1 MHz

3260B: 20 Hz to 1 MHz

### 3265BQ Measurement Frequency Range

3260B: 20 Hz to 3 MHz

### Basic Accuracy

$\pm$ 1%. Varies with measurement speed, frequency and impedance

### Measurement Terminals

2-terminal measurements using M8 studs

4-terminal measurements using Kelvin Clips connected to analyzer and heavy current cables from M8 studs

Measurement terminals internally protected by 1.6 A fuses against inductor back-EMF or accidental disconnection of inductor.

### Control Connections

9-way cable between rear panels of analyzer and 3265 unit controls the application of DC Bias Current and monitors the status of the instruments. Status data includes excessive voltage drop and over-temperature.

### 3265 Units in Parallel

Five 3265B units may be connected in parallel to give 125 A DC bias current with measurements up to 1 MHz.

Two 3265BQ units may be connected in parallel to give 50 A DC bias current with measurements up to 3 MHz.

### Interlock

Bias Safety Interlock socket on rear panel of analyzer provides door lock and closed control lines.

### Environmental conditions

This equipment is intended for indoor use only in a non-explosive and non-corrosive atmosphere

### Temperature range

Storage -40 °C to 70 °C

Operating 0 °C to 40 °C (20 A maximum)

Full Accuracy 15 °C to 30 °C (25 A maximum)

### Relative humidity

Up to 80% non-condensing

### Altitude

Up to 2000 m

### Installation category

II in accordance with IEC664

### Safety

Complies with the requirements of EN61010-1

### EMC

Complies with EN61326 for emissions and immunity

### AC Input Power

Input voltage: 90 to 255 VAC

Input frequency: 47 to 63 Hz

Input current: 9 A rms maximum

Power factor:  $>$ 0.9

Unit powers up automatically when connected to a powered analyzer. Isolating switch provided.

### Dimensions

Height 190 mm (7½")      Depth 525 mm (20½")

Width 440 mm (17¾")      Weight 18.5 kg (41 lb)

### Cooling

Fan cooled. Intake front, exhaust rear. Fan filter accessible on front panel. Over temperature trip.

### Order codes

#### Description

#### 3265B

1 MHz 25 A DC Bias Unit

#### 3265BQ

3 MHz 25 A DC Bias Unit

All units supplied with:-

User manual

4 x BNC to BNC link cables

9-way control cable

#### Order code

**1J3265B**

**1J3265BQ**

AC power cable

Spare fuses

### Accessories

#### Description

Kelvin Clips (Fine Jaw)

Kelvin Clips (Large Jaw)

High Current Bus Bar Set

250 A Fixture (Conventional)

250 A Fixture (Surface Mount)

125 A Fixture (Conventional)

125 A Fixture (Surface Mount)

#### Order code

1EVA40100

1EVA40180

4-324-6009-PAIR

1J1036

1J10362

1J1015

1J1016



### 绿测科技有限公司

广州总部：广州市番禺区陈边村金欧大道83号江潮创意园A栋208室  
深圳分公司：深圳市龙华区龙华街道 油松社区东环一路1号耀丰通工业园1-2栋2栋607  
南宁分公司：广西自由贸易试验区南宁片区五象大道401号五象航洋城1号楼3519号  
广州分公司：广州市南沙区凤凰大道89号中国铁建·凤凰广场B栋1201房  
电话：020-2204 2442  
传真：020-8067 2851  
邮箱：Sales@greentest.com.cn  
官网：www.greentest.com.cn



微信视频号



绿测科技订阅号



绿测工场服务号